



Warning: Illegal string offset 'small' in
/home/platne/serwer21911/public_html/copterx_pl/cache/3_1^%%5F^5F4^5F4AC088%%index.tpl.p
hp on line 18



CopterX (CX450EPP-V3) 450 Flybar Electronic Parts Package V3

Features:

- Just add a radio system and battery of your choice to complete your CopterX CX450 class helicopter
- High quality mini / standard servos for extra weight saving
- ESC feature build-in BEC for simple and clean installation
- High power 3550KV motor for long and reliable operation

CX-9G Specification:

- Operating Voltage: 4.8VDC-6.0V DC
- Operating Speed: 0.17sec/60 4.8V
- Output Torque: >1.0kgf-cm(14.0oz.in)at 4.8V
- Weight: 9.0g(0.28oz)
- Dimensions: 22.5*12.8*23.7mm(0.89x0.5x0.93in)

MG-D-9257-V2 Specification:

- Wire: 25cm
- Operating Voltage: 4.8v – 6v
- Operating Speed: 0.09sec/60° (4.8V) / 0.08sec/60° (6.0V)
- Stall Torque: 2.2kg-cm (4.8V) / 2.4kg-cm (6.0V)
- Pulse width: 1520us
- Working Frequency: 333Hz
- Size: 36 x 15.2 x 29mm
- Weight: 25g

CX-1X2000 Features:

- New direction switch (DIR), allows pilot to set the direction of the tail rotor servo
- New digital servo switch (DS), allows pilot to set it for either a digital servo or a non-digital servo
- NEW travel trim (LIMIT), allows pilot to set the amount of travel for the tail rotor servo
- Micro AVCS heading hold gyro
- Compact design to work most helicopter from 100-600 size
- Aluminum casing for accurate vibration free operation
- User selectable between AVCS or Normal mode
- Easily programmable without the aids of complex setup box
- Fully compatible from analog to narrow band digital servo (1.52ms analog, 1.52ms digital, 760us, 960us)
- Compatible with most popular PPM, PCM, 2.4G radio system
- Wide operation voltage from 3.5V to 10V DC

CX-1X2000 Specification:

- Weight: 11g (metal case, cables and plugs included)
- Operating Voltage: DC3.5V - 10V
- Operating Current Drain: 60ma
- Operating Temperature: -10°C - 50°C
- Maximal Angular Velocity: 800°/sec
- Servo Compatibility: 1.52ms analog servo, 1.52ms digital servo, 760us digital servo, 960us digital servo
- Radio Compatibility: PPM, PCM, 2.4G
- Dimensions: 22.2*22.2*11mm

CX-ESC-40A Specification:

- Cont. current: 40A
- Burst current(>10s): 55A
- BEC mode: Linear
- BEC output: 5V / 3A
- BEC output capability: 5 servos (2S Lipo) / 4 servos (3S Lipo)
- Battery cell: 2-3S (Lipo) / 5-9 cells (NiMH)
- Weight: 39g
- Dimension: 68*25*8mm

CX450-10-04 Specification:

- Weight: 79.6g
- Dimension: Ø28*50mm

Package Included:

- CopterX (CX-9G) 9G Servo X 3
- Fusionsic (MG-D-9257-V2) 9257 25g Metal Gear High Speed Mini Digital Servo
- CopterX (CX-1X2000) Mini Heading-Hold Gyro System
- CopterX (CX-ESC-40A) 40A V2 Brushless Electronic Speed Controller
- CopterX (CX450-10-04) 430XL Brushless Motor (3550KV)